

Protect BSK

HVAC Insulation: Protect, solutions for fire resistant ducts

ISOVER solutions for providing fire resistance in HVAC applications by using high performing ULTIMATE mineral wool and accessories. Protect Solutions are designed for providing fire protection to air ducts and smoke extraction ducts. Installation guidelines must be followed and ISOVER Protect components must be used (U Protect 4.0, BSF, BSK, Black Tape and fire screws).



Fire protection

Protect range provides effective fire resistance, but also very good performance in reaction to fire



Indoor air quality

ISOVER HVAC solutions help to reduce the sources of pollution as they comply with all existing requirements for indoor air quality



Fast Installation

ISOVER products are designed for ease and speed of installation





Protect BSK



HVAC Insulation: Protect, solutions for fire resistant ducts

Characteristic	Symbol	Unit	Quantities and measured values	Standard
Application field	-	-	ISOVER solutions for providing fire resistance in HVAC using Protect components. Protect solutions provide an easy to install and lightweight solution in fire classes EI15 - EI120.	EN 1366-1 EN 1366-8
Material	-	-	Inorganic adhesive Alkaline solution Free of Volatile Organic Compunds (VOCs)	-
Processing temperature	Т	°C	From + 5 to + 30	-
Behaviour in fire	-	-	Non-combustible	-
Storage/transport	-	-	Cold but frost protected Protect BSK has a normal shelf life time of 12 months	-
Packing	-	-	8 kg PP-bucket with lid 310 ml cartridges (12 units in a cardboard-box)	-
Instruction for use	-	-	Before use, the material must be stirred well Application by brush, roller or spatula The surface should be clean, dry, free of grease Hardening after approximately 12 hours under normal conditions (20 °C, 50 %RH) Possible variations depending on site conditions	-
Classification	-	-	According to Directive 67/548/EEC or Directive 1999/45/EC: not applicable	-

www.isover-technical-insulation.com

The technical information corresponds to our present state of knowledge and experience at the date of printing (see imprint). But no legal guarantee can be given, unless it has been explicitly agreed. The state of experience and knowledge is developing continuously. Please see to it that you always use the latest edition of this information. The described product applications do not take special circumstances in consideration. Please verify whether our products are appropriate for the concrete application. For further information please contact our Isover sales offices. We deliver only according to our terms of trade and terms of delivery.

